```
    }
}
```

❶ ProductId automatically binds to route values as it implements TryParse.

❷ ProductId is a C# 10 record struct.

❸ It implements TryParse, so it's treated as a simple type by minimal APIs.

❹ Checks that the string is not null and that the first character in the string is 'p' . . .

❺ and if it is, tries to parse the remaining characters as an integer

❻ Efficiently skips the first character by treating the string as a ReadOnlySpan

❼ If the string was parsed successfully, id contains the parsed value.

❽ Everything parsed successfully, so creates a new ProductId and returns true

❾ Something went wrong, so returns false and assigns a default value to the (unused) result

Using modern C# and .NET features

Listing 7.2 included some C# and .NET features that you may not have seen before, depending on your background:

- *Pattern matching for null values*—`s is not null`. Pattern matching features have been introduced gradually into C# since C# 7. The `is not null` pattern, introduced in C# 9, has some minor advantages over the common `!= null` expression. You can read all about pattern matching at http://mng.bz/gBxl.
- *Records and struct records*—`readonly record struct`. Records are syntactical sugar over normal `class` and `struct` declarations, which make declaring new types more succinct and provide convenience methods for working with immutable types. Record structs were introduced in C# 10. You can read more at http://mng.bz/5wWz.
- `Span<T>` *for performance*—`s.AsSpan()`. `Span<T>` and `ReadOnlySpan<T>` were introduced in .NET Core 2.1 and are particularly useful for reducing allocations when working with `string` values. You can read more about them at http://mng.bz/6DNy.