Useful .NET CLI (`dotnet`) commands: Use `--help` to see all the optional arguments

Command	Run from	Description
`dotnet restore`	Solution folder	Restores the NuGet packages for all the projects in the solution.
`dotnet build`	Solution folder	Builds all the projects in the solution. To build in `Release` mode, use the `-c` switch.
`dotnet run`	Project folder	Runs the project in the current folder. Use during development to run your app.
`dotnet publish -c Release -o <Folder>`	Project folder	Publishes the project to the provided folder. Copies all the required files to the provided output folder so it can be deployed.
`dotnet test`	Solution folder	Restores packages, builds, and executes any unit tests found in the solution. Requires the .NET Test SDK and a testing framework adapter (see chapter 35).
`dotnet add package <Name>`	Project folder	Install the NuGet package with the provided name in the current project. Optionally specify a package version—for example, `-v 2.1.0`.
`dotnet new --list`	Anywhere	View all the installed templates for creating ASP.NET Core apps, libraries, test projects, solution files, and many more.
`dotnet new <Template> -o <Folder> -n <NewName>`	Anywhere; empty folder for new projects	Create a new item from the provided template, specifying the folder in which to place the item and the name for the item.
`dotnet --info`	Anywhere	Displays information about the .NET SDKs and runtimes installed on your machine.
`dotnet jwts create`	Project folder	Creates a JWT for calling API applications protected with OAuth. You can also customize the token and view existing tokens (see chapter 25).
`dotnet ef addmigrations <Name>`	Project folder	Adds a new EF Core migration to the project with the provided name. Requires the EF Core global tool (see Chapter 12).
`dotnet ef database update`	Project folder	Apply pending EF Core migrations to a database. Warning: this will modify your database!