WebApplicationBuilder adds several default configuration providers to the `ConfigurationManager`, which we'll look at in more detail throughout this chapter:

- *JSON file provider*—Loads settings from an optional JSON file called appsettings.json. It also loads settings from an optional environment-specific JSON file called appsettings.*ENVIRONMENT*.json. I show how to use environment-specific files in section 10.4.
- *User Secrets*—Loads secrets that are stored safely during development.
- *Environment variables*—Loads environment variables as configuration variables, which are great for storing secrets in production.
- *Command-line arguments*—Uses values passed as arguments when you run your app.

The `ConfigurationManager` is configured with all these sources automatically, but you can easily add more providers. You can also start from scratch and clear the default providers as shown in the following listing, which completely customizes where configuration is loaded from.

Listing 10.3 Loading appsettings.json by clearing the configuration sources

```
WebApplicationBuilder builder = WebApplication.CreateBuilder(args);

builder.Configuration.Sources.Clear();                                    ❶
builder.Configuration.AddJsonFile("appsettings.json", optional: true);    ❷

WebApplication app = builder.Build();

app.MapGet("/", () => app.Configuration.AsEnumerable());                  ❸

app.Run();
```

❶ Clears the providers configured by default in WebApplicationBuilder

❷ Adds a JSON configuration provider, providing the name of the configuration file