`http://` requests, whereas `https` listens for both `http://` and `https://`. The `IIS Express` profile can be used only in Windows and uses IIS Express to run your application.

Listing 10.16 A typical launchSettings.json file defining three profiles

```
{
  "iisSettings": {                                                    ❶
    "windowsAuthentication": false,                                   ❶
    "anonymousAuthentication": true,                                  ❶
    "iisExpress": {                                                   ❶
      "applicationUrl": "http://localhost:53846",                     ❶
      "sslPort": 44399                                                ❶
    }
  },
  "profiles": {
    "http": {                                                         ❷
      "commandName": "Project",                                       ❸
      "dotnetRunMessages": true,                                      ❹
      "launchBrowser": true,                                          ❺
      "applicationUrl": "http://localhost:5063",                      ❻
      "environmentVariables": {                                       ❼
        "ASPNETCORE_ENVIRONMENT": "Development"                       ❼
      }                                                               ❼
    },
    "https": {                                                        ❽
      "commandName": "Project",
      "dotnetRunMessages": true,
      "launchBrowser": true,
      "applicationUrl": "https://localhost:7202;http://localhost:5063",  ❾
      "environmentVariables": {
        "ASPNETCORE_ENVIRONMENT": "Development"
      }
    },
    "IIS Express": {                                                  ❿
      "commandName": "IISExpress",
      "launchBrowser": true,
      "environmentVariables": {                                       ⓫
        "ASPNETCORE_ENVIRONMENT": "Development"                       ⓫
      }                                                               ⓫
    }
  }
}
```

❶ Defines settings for running behind IIS or using the IIS Express profile