The OpenAPI document includes a general description of your app, such as a title and version, as well as specific details about each of the endpoints. In figure 11.2, for example, the `/fruit/{id}` endpoint describes the fact that it needs a `GET` verb and takes an `id` parameter in the path.

You can change some of the document values, such as the title, by adding configuration to the `AddSwaggerGen()` method. You can set the title of the app to `"Fruitify"` and add a description for the document:

```
builder.Services.AddSwaggerGen(x =>
    x.SwaggerDoc("v1", new OpenApiInfo()
    {
        Title = "Fruitify",
        Description = "An API for interacting with fruit stock",
        Version = "1.0"
    }));
```

You can also change settings such as the path used to expose the document and various minutia about how Swashbuckle generates the final JSON. See the documentation for details: http://mng.bz/OxQR.

All that is clever, but if you're shrugging and asking "So what?", where OpenAPI *really* shines is the hooks it provides for other tooling. And you've already added one such piece of tooling to your app: Swagger UI.

11.2 Testing your APIs with Swagger UI

In this section you'll learn about Swagger UI (https://swagger.io/tools/swagger-ui), an open-source web UI that makes it easy to visualize and test your OpenAPI apps. In some ways you can think of Swagger UI as being a light version of Postman, which I used in previous chapters to interact with minimal API applications. Swagger UI provides an easy way to view all the endpoints in your application and send requests to them. Postman provides many extra features, such as creating collections and sharing them with your team, but if all you're trying to do is test your application locally, Swagger UI is a great option.