```
          buildtransitive</IncludeAssets>
    </PackageReference>
  </ItemGroup>

</Project>
```

❶ Defines where the OpenAPI description was loaded from and code generation settings

❷ Extra NuGet packages are required by the code generator.

Theoretically, this code should be everything you need to generate the client. Unfortunately, Visual Studio adds some out-of-date packages that you'll need to update before your project will build, as follows:

1. Update NSwag.ApiDescription.Client to the latest version (currently, 13.18.2). This package does the code generation based on the OpenAPI description.
2. Update Microsoft.Extensions.ApiDescription.Client to the latest version (7.0.0 at the time of the .NET 7 release). This package is referenced transitively by NSwag.ApiDescription.Client anyway, so you don't have to reference it directly, but doing so ensures that you have the latest version of the package.

NOTE By default, the generated client uses Newtonsoft.Json to serializes the requests and responses. In section 11.4.4 you'll see how to replace it with the built-in System.Text.Json.

After you make these changes, your project should look similar to the following listing.

Listing 11.4 Updating package versions for OpenAPI generation

```
<Project Sdk="Microsoft.NET.Sdk">

  <PropertyGroup>
    <OutputType>Exe</OutputType>
    <TargetFramework>net7.0</TargetFramework>
    <ImplicitUsings>enable</ImplicitUsings>
    <Nullable>enable</Nullable>
  </PropertyGroup>
  <ItemGroup>
    <OpenApiReference
```