```
        Include="OpenAPIs\swagger.json"
        CodeGenerator="NSwagCSharp"
        Namespace="Fruit"
        ClassName="FruitClient">
      <SourceUri>https://localhost:7186/swagger/v1/swagger.json</SourceUri>
    </OpenApiReference>
  </ItemGroup>

  <ItemGroup>
    <PackageReference
      Include="Microsoft.Extensions.ApiDescription.Client"
      Version="7.0.0">                                                    ❶
      <PrivateAssets>all</PrivateAssets>
      <IncludeAssets>runtime; build; native; contentfiles; analyzers;
        buildtransitive</IncludeAssets>
    </PackageReference>
    <PackageReference Include="Newtonsoft.Json" Version="13.0.1" />
    <PackageReference Include="NSwag.ApiDescription.Client"
      Version="13.18.2">                                                  ❶
      <PrivateAssets>all</PrivateAssets>
      <IncludeAssets>runtime; build; native; contentfiles; analyzers;
        buildtransitive</IncludeAssets>
    </PackageReference>
  </ItemGroup>

</Project>
```

❶ Updates to the latest version

With the packages updated, you can build your project and generate the `FruitClient`. In section 11.4.3 you'll see how to use this client to call your API, but first we'll look at how to generate the client with a .NET global tool if you're not using Visual Studio.

11.4.2 Generating a client using the .NET Global tool

In this section you'll learn how to generate a client from an OpenAPI definition by using a .NET global tool instead of Visual Studio. The result is essentially the same, so if you've followed the steps in section 11.4.1 in Visual Studio, you can skip this section.

NOTE You don't have to use Visual Studio or a .NET tool. Ultimately ,you need a csproj file that looks like listing 11.4 and an OpenAPI definition JSON file in your project, so if you're happy editing the project file and downloading the