- `/JsonLibrary:SystemTextJson`—This switch specifies the JSON serialization library to use. It defaults to using Newtonsoft.Json.

TIP A vast number of configuration options is available for NSwag. I find that the best documentation is available in the NSwag .NET tool. You can install the tool by using `dotnet tool install -g NSwag.ConsoleCore`, and you can view the available options by running `nswag help openapi2csclient`.

You can set all three of these options by adding an `<Options>` element to the `<OpenApiReference>` element, as shown in the following listing. Make sure that you open and close both elements correctly so the XML stays valid; it's an easy mistake to make when editing by hand!

Listing 11.7 Customizing NSwag generator options

```
<OpenApiReference Include="OpenAPIs\fruit.json"
  SourceUrl="http://localhost:5062/swagger/v1/swagger.json"
  Namespace="Fruit"
  ClassName="FruitClient" >
    <Options>/UseBaseUrl:false /GenerateClientInterfaces:true
  ➥ /JsonLibrary:SystemTextJson</Options>     ❶
</OpenApiReference>                            ❷
```

❶ Customizes the options NSwag uses for code generation

❷ Make sure to close the outer XML element to keep the XML valid.

You'd be forgiven for thinking that after making these changes, NSwag would update the generated code next time you build. Unfortunately, it's not necessarily that simple. NSwag watches for changes to the OpenAPI description JSON file saved in your project and will regenerate the code any time the file changes, but it won't necessarily update when you change options in your csproj file. Even worse, doing a clean or rebuild similarly has no effect. If you find yourself in this situation, it's best to delete the obj folder for your project to ensure that everything regenerates correctly.