After updating your OpenAPI description by using either Visual Studio or the .NET tool, build your application to trigger NSwag to regenerate your client. Any changes you made to your OpenAPI description (such as adding operation IDs) will be reflected in the generated code.

I think that client generation is the killer app for OpenAPI descriptions, but it works best when you use metadata to add extensive documentation to your APIs. In section 11.5 you'll learn how to go one step further by adding summaries and descriptions to your endpoints.

11.5 Adding descriptions and summaries to your endpoints

In this section you'll learn how to add extra descriptions and summaries to your OpenAPI description document. Tools such as Swagger UI and NSwag use these extra descriptions and summaries to provide a better developer experience working with your API. You'll also learn about alternative ways to add metadata to your minimal API endpoints.

11.5.1 Using fluent methods to add descriptions

Whilst working with your minimal API endpoints and calling methods such as `WithName()` and `WithTags()`, you may have noticed the methods `WithSummary()` and `WithDescription()`. These methods add metadata to your endpoint in exactly the same way as the other `With*` methods, but unfortunately, they don't update your OpenAPI description without some extra changes.

To make use of the summary and description metadata, you must add an extra NuGet package, Microsoft.AspNetCore.OpenApi, and call `WithOpenApi()` on your endpoint. This method ensures that the summary and description