metadata are added correctly to the OpenAPI description when Swashbuckle generates the document. Add this package via the NuGet package manager or the .NET CLI by calling

```
dotnet add package Microsoft.AspNetCore.OpenApi
```

from the project folder. Then update your endpoints to add summaries and/or descriptions, making sure to call `WithOpenApi()`, as shown in the following listing.

Listing 11.9 Adding summaries and descriptions to endpoints using `WithOpenApi()`

```
using System.Collections.Concurrent;

WebApplicationBuilder builder = WebApplication.CreateBuilder(args);

builder.Services.AddEndpointsApiExplorer();
builder.Services.AddSwaggerGen();

WebApplication app = builder.Build();

app.UseSwagger();
app.UseSwaggerUI();

var _fruit = new ConcurrentDictionary<string, Fruit>();

app.MapGet("/fruit/{id}", (string id) =>
    _fruit.TryGetValue(id, out var fruit)
        ? TypedResults.Ok(fruit)
        : Results.Problem(statusCode: 404))
    .WithName("GetFruit")
    .WithTags("fruit")
    .Produces<Fruit>()
    .ProducesProblem(404)
    .WithSummary("Fetches a fruit")                                  ❶
    .WithDescription("Fetches a fruit by id, or returns 404" +       ❷
      " if no fruit with the ID exists")                             ❷
    .WithOpenApi();                                                  ❸

app.Run();
record Fruit(string Name, int Stock);
```

❶ Adds a summary to the endpoint

❷ Adds a description to the endpoint