```
    [Tags("fruit")]                                                    ❺
    public IResult GetFruit(string id)
        => _fruit.TryGetValue(id, out var fruit)
            ? TypedResults.Ok(fruit)
            : Results.Problem(statusCode: 404);
}
```

❶ Enables XML comments for your OpenAPI descriptions

❷ You must use static or instance handlers, not lambda methods.

❸ You can add extra metadata by using methods.

❹ The XML comments are used in the OpenAPI description.

❺ You can also add extra metadata by using attributes on the handler method.

I like the XML comment approach, as it feels much more natural for C# and the comments are often deemphasized in IDEs, reducing visual clutter. You'll still need to use attributes and/or fluent methods to fully describe your endpoints for OpenAPI, but every little bit helps!

As I've mentioned several times, how far you go with your OpenAPI description is up to you and how much value you get from it. If you want to use OpenAPI only for local testing with Swagger UI, it doesn't make sense to clutter your code with lots of extra metadata. In fact, in those cases it would be best to add the swagger services and middleware conditionally only when you're in development, as in this example:

```
WebApplicationBuilder builder = WebApplication.CreateBuilder(args);

if(builder.Environment.IsDevelopment())
{
    builder.Services.AddEndpointsApiExplorer();
    builder.Services.AddSwaggerGen();
}

WebApplication app = builder.Build();
if(app.Environment.IsDevelopment())
{
    app.UseSwagger();
    app.UseSwaggerUI();
}

app.Run();
```