and how they generate HTML.

13.1.3 Generating HTML with Razor Pages

When an ASP.NET Core application receives a request, it progresses through the middleware pipeline until a middleware component handles it. Normally, the routing middleware matches a request URL's path to a configured route, which defines which Razor Page to invoke, and the endpoint middleware invokes it.

Razor Pages are stored in .cshtml files (a portmanteau of .cs and .xhtml) within the Pages folder of your project. In general, the routing middleware maps request URL paths to a single Razor Page by looking in the Pages folder of your project for a Razor Page with the same path. If you look back at figure 13.3, for example, you see that the Privacy page of your app corresponds to the path `/Privacy` in the browser's address bar. If you look inside the Pages folder of your project, you'll find the Privacy.cshtml file, shown in the following listing.

Listing 13.3 The Privacy.cshtml Razor Page

```
@page                                                          ❶
@model PrivacyModel                                            ❷
@{
    ViewData["Title"] = "Privacy Policy";                      ❸
}
<h1>@ViewData["Title"]</h1>                                    ❹

<p>Use this page to detail your site's privacy policy.</p>     ❺
```

❶ Indicates that this is a Razor Page

❷ Links the Razor Page to a specific PageModel

❸ C# code that doesn't write to the response

❹ HTML with dynamic C# values written to the response