selects the View.cshtml Razor Page as the endpoint for the request, and the `EndpointMiddleware` executes the page's handler when the request reaches it in the middleware pipeline.

NOTE Remember that routing is not case-sensitive, so the request URL will match even if it has a different URL casing from the route template.

In chapter 13 you learned that Razor Page handlers are the methods that are invoked on a Razor Page, such as `OnGet`. When we say "a Razor Page is executed," we really mean "an instance of the Razor Page's `PageModel` is created, and a page handler on the model is invoked." Razor Pages can have multiple page handlers, so once the `RoutingMiddleware` selects a Razor Page, the `EndpointMiddleware` still needs to choose which handler to execute. You'll learn how the framework selects which page handler to invoke in chapter 15.

By default, each Razor Page creates a single route template based on its file path. The exception to this rule is for Razor Pages that are called Index.cshtml. Index.cshtml pages create two route templates, one ending with `"Index"` and the other without this suffix. If you have a Razor Page at the path `Pages/ToDo/Index.cshtml`, you have two route templates that point to the same page:

- `"ToDo"`
- `"ToDo/Index"`

When either of these routes is matched, the same Index.cshtml Razor Page is selected. If your application is running at the URL https://example.org, you can view the page by executing https://example.org/ToDo or https://example.org/ToDo/Index.