NOTE The async suffix naming convention is suggested by Microsoft, though it is unpopular with some developers. NServiceBus provides a reasoned argument against it here (along with Microsoft's advice): http://mng.bz/e59P.

Based on this convention, we can now identify what type of request each page handler in listing 15.1 corresponds to:

- `OnGet`—Invoked for `GET` requests that don't specify a `handler` value
- `OnPostAsync`—Invoked for `POST` requests that don't specify a `handler` value; returns a `Task`, so it uses the `Async` suffix, which is ignored for routing purposes
- `OnPostCustomSearch`—Invoked for `POST` requests that specify a `handler` value of `"CustomSearch"`

The Razor Page in listing 15.1 specifies three handlers, so it can handle only three verb-handler pairs. But what happens if you get a request that doesn't match these, such as a request using the `DELETE` verb, a `GET` request with a nonblank `handler` value, or a `POST` request with an unrecognized `handler` value?

For all these cases, the `EndpointMiddleware` executes an implicit page handler instead. *Implicit* page handlers contain no logic; they simply render the Razor view. For example, if you sent a `DELETE` request to the Razor Page in listing 15.1, the `EndpointMiddleware` would execute an implicit handler. The implicit page handler is equivalent to the following handler code:

```
public void OnDelete() { }
```