```
    public void OnGet()                                                    ❹
    {                                                                      ❹
    }                                                                      ❹

    public IActionResult OnPost(int max)                                   ❺
    {
        if (ModelState.IsValid)                                            ❻
        {                                                                  ❻
            Results = _searchService.Search(Input.SearchTerm, max);        ❻
            return Page();                                                 ❻
        }                                                                  ❻
        return RedirectToPage("./Index");                                  ❻
    }
}
```

❶ The SearchService is injected from DI for use in page handlers.

❷ Properties decorated with the [BindProperty] attribute are model-bound.

❸ Undecorated properties are not model-bound.

❹ The page handler doesn't need to check if the model is valid. Returning void renders the view.

❺ The max parameter is model-bound using values in the request.

❻ If the request was not valid, the method indicates the user should be redirected to the Index page.

In this example, the `OnGet` handler doesn't require any parameters, and the method is simple: it returns `void`, which means the associated Razor view will be rendered. It could also have returned a `PageResult`; the effect would have been the same. Note that this handler is for HTTP `GET` requests, so the `Input` property decorated with `[BindProperty]` is not bound.

TIP To bind properties for `GET` requests too, use the `SupportsGet` property of the attribute, as in `[BindProperty(SupportsGet = true)]`.

The `OnPost` handler, conversely, accepts a parameter `max` as an argument. In this case it's a simple type, `int`, but it could also be a complex