URL (route values)	HTTP body data (form values)	Parameter values bound
`/GBP/USD`		`currencyIn=GBP currencyOut=USD qty=0`
`/GBP/USD?currencyIn=CAD`	`QTY=50`	`currencyIn=GBP currencyOut=USD qty=50`
`/GBP/USD?qty=100`	`qty=50`	`currencyIn=GBP currencyOut=USD qty=50`
`/GBP/USD?qty=100`	`currencyIn=CAD& currencyOut=EUR&qty=50`	`currencyIn=CAD currencyOut=EUR qty=50`

For each example, be sure you understand *why* the bound values have the values that they do. In the first example, the `qty` value isn't found in the form data, in the route values, or in the query string, so it has the default value of `0`. In each of the other examples, the request contains one or more duplicated values; in these cases, it's important to bear in mind the order in which the model binder consults the binding sources. By default, form values will take precedence over other binding sources, including route values!

NOTE The default model binder isn't case-sensitive, so a binding value of `QTY=50` will happily bind to the `qty` parameter.

Although this may seem a little overwhelming, it's relatively unusual to be binding from all these different sources at once. It's more common to have your values all come from the request body as form values, maybe with an ID from URL route values. This scenario serves as more of a cautionary tale about the knots you can twist yourself into if you're not sure how things work under the hood.

In these examples, you happily bound the `qty` integer property to incoming values, but as I mentioned earlier, the values stored in binding sources are all strings. What types can you convert a string to?