As you've already seen, by default the ASP.NET Core model binder attempts to bind your binding models from three binding sources: form data, route data, and the query string.

Occasionally, you may find it necessary to specifically declare which binding source to bind to. In other cases, these three sources won't be sufficient at all. The most common scenarios are when you want to bind a method parameter to a request header value or when the body of a request contains JSON-formatted data that you want to bind to a parameter. In these cases, you can decorate your binding models with attributes that say where to bind from, as shown in the following listing.

Listing 16.5 Choosing a binding source for model binding

```
public class PhotosModel: PageModel
{
    public void OnPost(
        [FromHeader] string userId,        ❶
        [FromBody] List<Photo> photos)     ❷
    {
        /* method implementation */
    }
}
```

❶ The userId is bound from an HTTP header in the request.

❷ The list of photo objects is bound to the body of the request, typically in JSON format.

In this example, a page handler updates a collection of photos with a user ID. There are method parameters for the ID of the user to be tagged in the photos, `userId`, and a list of `Photo` objects to tag, `photos`.

Rather than binding these method parameters using the standard binding sources, I've added attributes to each parameter, indicating the binding source to use. The `[FromHeader]` attribute has been applied to the `userId` parameter. This tells the model binder to bind the value to an HTTP request header value called `userId`.