We're also binding a list of photos to the body of the HTTP request by using the `[FromBody]` attribute. This tells the binder to read JSON from the body of the request and bind it to the `List<Photo>` method parameter.

WARNING Developers coming from .NET Framework and the legacy version of ASP.NET should take note that the `[FromBody]` attribute is explicitly required when binding to JSON requests in Razor Pages. This differs from the legacy ASP.NET behavior, in which no attribute was required.

You aren't limited to binding JSON data from the request body. You can use other formats too, depending on which `InputFormatter`s you configure the framework to use. By default, only a JSON input formatter is configured. You'll see how to add an XML formatter in chapter 20, when I discuss web APIs.

TIP Automatic binding of multiple formats from the request body is one of the features specific to Razor Pages and MVC controllers, which is missing from minimal APIs.

You can use a few different attributes to override the defaults and to specify a binding source for each binding model (or each property on the binding model). These are the same attributes you used in chapter 7 with minimal APIs:

- `[FromHeader]`—Bind to a header value.
- `[FromQuery]`—Bind to a query string value.
- `[FromRoute]`—Bind to route parameters.
- `[FromForm]`—Bind to form data posted in the body of the request. This attribute is not available in minimal APIs.
- `[FromBody]`—Bind to the request's body content.