You can apply each of these to any number of handler method parameters or properties, as you saw in listing 16.5, with the exception of the `[FromBody]` attribute. Only one value may be decorated with the `[FromBody]` attribute. Also, as form data is sent in the body of a request, the `[FromBody]` and `[FromForm]` attributes are effectively mutually exclusive.

TIP Only one parameter may use the `[FromBody]` attribute. This attribute consumes the incoming request as HTTP request bodies can be safely read only once.

As well as these attributes for specifying binding sources, there are a few attributes for customizing the binding process even further:

- `[BindNever]`—The model binder will skip this parameter completely. You can use this attribute to prevent mass assignment, as discussed in these two posts on my blog: http://mng.bz/QvfG and http://mng.bz/Vd90.
- `[BindRequired]`—If the parameter was not provided or was empty, the binder will add a validation error.
- `[FromServices]`—This is used to indicate the parameter should be provided using dependency injection (DI). This attribute isn't required in most cases, as .NET 7 is smart enough to know that a parameter is a service registered in DI, but you can be explicit if you prefer.

In addition, you have the `[ModelBinder]` attribute, which puts you into "God mode" with respect to model binding. With this attribute, you can specify the exact binding source, override the name of the parameter to bind to, and specify the type of binding to perform. It'll be rare that you need this one, but when you do, at least it's there!