If you had to write this validation code fresh for every app, it would be tedious and likely error-prone. Luckily, you can use `DataAnnotations` attributes to declaratively describe the validation requirements for your binding models. The following listing, first shown in chapter 7, shows how you can decorate a binding model with various validation attributes. This expands on the example you saw earlier in listing 16.4.

Listing 16.6 Adding `DataAnnotations` to a binding model to provide metadata

```
public class UserBindingModel
{
    [Required]                                  ❶
    [StringLength(100)]                         ❷
    [Display(Name = "Your name")]               ❸
    public string FirstName { get; set; }

    [Required]
    [StringLength(100)]
    [Display(Name = "Last name")]
    public string LastName { get; set; }

    [Required]
    [EmailAddress]                              ❹
    public string Email { get; set; }

    [Phone]                                     ❺
    [Display(Name = "Phone number")]
    public string PhoneNumber { get; set; }
}
```

❶ Values marked Required must be provided.

❷ The StringLengthAttribute sets the maximum length for the property.

❸ Customizes the name used to describe the property

❹ Validates that the value of Email is a valid email address

❺ Validates that the value of PhoneNumber has a valid telephone format

For validation requirements that don't lend themselves to attributes, such as when the validity of one property depends on the value of another, you can implement `IValidatableObject`, as described in chapter 7.