will not route requests to the page, and the file is ignored for most purposes.

DEFINITION A *directive* is a statement in a Razor file that changes the way the template is parsed or compiled. Another common directive is the `@using newNamespace` directive, which makes objects in the `newNamespace` namespace available.

The code-behind .cshtml.cs file contains the `PageModel` for an associated Razor Page. It contains the page handlers that respond to requests, and it is where the Razor Page typically interacts with other parts of your application.

Even though the .cshtml and .cshtml.cs files have the same name, such as ToDoItem.cshtml and ToDoItem.cshtml.cs, it's not the filename that's linking them. But if it's not by filename, how does the Razor Pages framework know which `PageModel` is associated with a given Razor Page view file?

At the top of each Razor Page, after the `@page` directive, is the `@model` directive with a `Type`, indicating which `PageModel` is associated with the Razor view. The following directives indicate that the `ToDoItemModel` is the `PageModel` associated with the Razor Page:

```
@page
@model ToDoItemModel
```

Once a request is routed to a Razor Page, as covered in chapter 14, the framework looks for the `@model` directive to decide which `PageModel` to use. Based on the `PageModel` selected, it then binds to any properties in the `PageModel` marked with the `[BindProperty]` attribute (as we covered in chapter 16) and executes the appropriate page handler (based on the request's HTTP verb, as described in chapter 15).