Listing 17.13 Rendering a partial view from a Razor Page

```
@page                                          ❶
@model RecentToDoListModel                     ❷

@foreach(var todo in Model.RecentItems)        ❸
{
    <partial name="_ToDo" model="todo" />      ❹
}
```

❶ This is a Razor Page, so it uses the @page directive. Partial views do not use @page.

❷ The PageModel contains the list of recent items to render.

❸ Loops through the recent items. todo is a ToDoItemViewModel, as required by the partial view.

❹ Uses the partial tag helper to render the _ToDo partial view, passing in the model to render

When you render a partial view without providing an absolute path or file extension, such as `_ToDo` in listing 17.13, the framework tries to locate the view by searching the Pages folder, starting from the Razor Page that invoked it. For example, if your Razor Page is located at `Pages/Agenda/ToDos/RecentToDos.chstml`, the framework would look in the following places for a file called _ToDo.chstml:

- Pages/Agenda/ToDos/ (the current Razor Page's folder)
- Pages/Agenda/
- Pages/
- Pages/Shared/
- Views/Shared/

The first location that contains a file called _ToDo.cshtml will be selected. If you include the .cshtml file extension when you reference the partial view, the framework will look only in the current Razor Page's folder. Also, if you provide an absolute path to the partial, such as `/Pages/Agenda/ToDo.cshtml`, that's the only place the framework will look.