```
        <input class="form-control" asp-for="Quantity" />          ❸
        <span asp-validation-for="Quantity"></span>                ❹
    </div>
    <div class="form-group">
        <label asp-for="CurrencyTo"></label>                       ❷
        <input class="form-control" asp-for="CurrencyTo" />        ❸
        <span asp-validation-for="CurrencyTo"></span>              ❹
    </div>
    <button type="submit" class="btn btn-primary">Submit</button>
</form>
```

❶ This is the view for the Razor Page Convert.cshtml. The Model type is ConvertModel.

❷ asp-for on Labels generates the caption for labels based on the view model.

❸ asp-for on Inputs generates the correct type, value, name, and validation attributes for the model.

❹ Validation messages are written to a span using Tag Helpers.

At first glance, you might not even spot the Tag Helpers, they blend in so well with the HTML! This makes it easy to edit the files with any standard HTML text editor. But don't be concerned that you've sacrificed readability in Visual Studio. As you can see in figure 18.2, elements with Tag Helpers are distinguishable from the standard HTML `<div>` element and the standard HTML `class` attribute on the `<input>` element. The C# properties of the view model being referenced (`CurrencyFrom`, in this case) are also displayed differently from "normal" HTML attributes. And of course you get IntelliSense, as you'd expect. Most other integrated development environments *(*IDEs) also include syntax highlighting and IntelliSense support.