Imagine you're building the checkout page for the currency converter application, and you need to capture the user's details on the checkout page. In chapter 16 you built a `UserBindingModel` model (shown in listing 18.2), added `DataAnnotations` attributes for validation, and saw how to model-bind it in a `POST` to a Razor Page. In this chapter you'll see how to create the view for it by exposing the `UserBindingModel` as a property on your `PageModel`.

WARNING With Razor Pages, you often expose the same object in your view that you use for model binding. When you do this, you must be careful to not include sensitive values (that shouldn't be edited) in the binding model, to prevent mass-assignment attacks on your app. You can read more about these attacks on my blog at http://mng.bz/RXw0.

Listing 18.2 `UserBindingModel` for creating a user on a checkout page

```
public class UserBindingModel
{
    [Required]
    [StringLength(100, ErrorMessage = "Maximum length is {1}")]
    [Display(Name = "Your name")]
    public string FirstName { get; set; }

    [Required]
    [StringLength(100, ErrorMessage = "Maximum length is {1}")]
    [Display(Name = "Last name")]
    public string LastName { get; set; }

    [Required]
    [EmailAddress]
    public string Email { get; set; }

    [Phone(ErrorMessage = "Not a valid phone number.")]
    [Display(Name = "Phone number")]
    public string PhoneNumber { get; set; }
}
```

The `UserBindingModel` is decorated with various `DataAnnotations` attributes. In chapter 16 you saw that these attributes are used during model validation when the model is bound to a request, before the