Figure 18.4 The checkout page for an application. The HTML is generated based on a `UserBindingModel`, using Tag Helpers to render the required element values, input types, and validation messages.

The Razor template to generate this page is shown in listing 18.3. This code uses a variety of tag helpers, including

- A Form Tag Helper on the `<form>` element
- Label Tag Helpers on the `<label>`
- Input Tag Helpers on the `<input>`
- Validation Message Tag Helpers on `<span>` validation elements for each property in the `UserBindingModel`

Listing 18.3 Razor template for binding to `UserBindingModel` on the checkout page

```
@page
@model CheckoutModel                                                    ❶
@{
    ViewData["Title"] = "Checkout";
}
<h1>@ViewData["Title"]</h1>
<form asp-page="Checkout">                                              ❷
    <div class="form-group">
        <label asp-for="Input.FirstName"></label>                       ❸
        <input class="form-control" asp-for="Input.FirstName" />
        <span asp-validation-for="Input.FirstName"></span>
    </div>
    <div class="form-group">
        <label asp-for="Input.LastName"></label>
        <input class="form-control" asp-for="Input.LastName" />
        <span asp-validation-for="Input.LastName"></span>
    </div>
    <div class="form-group">
        <label asp-for="Input.Email"></label>
        <input class="form-control" asp-for="Input.Email" />            ❹
        <span asp-validation-for="Input.Email"></span>
    </div>
    <div class="form-group">
        <label asp-for="Input.PhoneNumber"></label>
        <input class="form-control" asp-for="Input.PhoneNumber" />
        <span asp-validation-for="Input.PhoneNumber"></span>            ❺
```