```
    </div>
    <button type="submit" class="btn btn-primary">Submit</button>
</form>
```

❶ The CheckoutModel is the PageModel, which exposes a UserBindingModel on the Input property.

❷ Form Tag Helpers use routing to determine the URL the form will be posted to.

❸ The Label Tag Helper uses DataAnnotations on a property to determine the caption to display.

❹ The Input Tag Helper uses DataAnnotations to determine the type of input to generate.

❺ The Validation Tag Helper displays error messages associated with the given property.

You can see the HTML markup that this template produces in listing 18.4, which renders in the browser as you saw in figure 18.4. You can see that each of the HTML elements with a Tag Helper has been customized in the output: the `<form>` element has an `action` attribute, the `<input>` elements have an `id` and `name` based on the name of the referenced property, and both the `<input>` and `<span>` have `data-*` attributes for validation.

Listing 18.4 HTML generated by the Razor template on the checkout page

```
<form action="/Checkout" method="post">
  <div class="form-group">
    <label for="Input_FirstName">Your name</label>
    <input class="form-control" type="text"
      data-val="true" data-val-length="Maximum length is 100"
      id="Input_FirstName" data-val-length-max="100"
      data-val-required="The Your name field is required."
      Maxlength="100" name="Input.FirstName" value="" />
    <span data-valmsg-for="Input.FirstName"
      class="field-validation-valid" data-valmsg-replace="true"></span>
  </div>
  <div class="form-group">
    <label for="Input_LastName">Your name</label>
    <input class="form-control" type="text"
      data-val="true" data-val-length="Maximum length is 100"
      id="Input_LastName" data-val-length-max="100"
      data-val-required="The Your name field is required."
      Maxlength="100" name="Input.LastName" value="" />
    <span data-valmsg-for="Input.LastName"
      class="field-validation-valid" data-valmsg-replace="true"></span>
  </div>
  <div class="form-group">
    <label for="Input_Email">Email</label>
    <input class="form-control" type="email" data-val="true"
      data-val-email="The Email field is not a valid e-mail address."
      Data-val-required="The Email field is required."
      Id="Input_Email" name="Input.Email" value="" />
```