```
    <span class="text-danger field-validation-valid"
      data-valmsg-for="Input.Email" data-valmsg-replace="true"></span>
    </div>
  <div class="form-group">
    <label for="Input_PhoneNumber">Phone number</label>
    <input class="form-control" type="tel" data-val="true"
      data-val-phone="Not a valid phone number." Id="Input_PhoneNumber"
      name="Input.PhoneNumber" value="" />
    <span data-valmsg-for="Input.PhoneNumber"
      class="text-danger field-validation-valid"
      data-valmsg-replace="true"></span>
  </div>
  <button type="submit" class="btn btn-primary">Submit</button>
  <input name="__RequestVerificationToken" type="hidden"
    value="CfDJ8PkYhAINFx1JmYUVIDWbpPyy_TRUNCATED" />
</form>
```

Wow, that's a lot of markup! If you're new to working with HTML, this might all seem a little overwhelming, but the important thing to notice is that you didn't have to write most of it! The Tag Helpers took care of most of the plumbing for you. That's basically Tag Helpers in a nutshell; they simplify the fiddly mechanics of building HTML forms, leaving you to concentrate on the overall design of your application instead of writing boilerplate markup.

NOTE If you're using Razor to build your views, Tag Helpers will make your life easier, but they're entirely optional. You're free to write raw HTML without them or to use the legacy HTML Helpers.

Tag Helpers simplify and abstract the process of HTML generation, but they generally try to do so without getting in your way. If you need the final generated HTML to have a particular attribute, you can add it to your markup. You can see that in the previous listings where `class` attributes are defined on `<input>` elements, such as `<input class="form-control" asp-for="Input.FirstName" />`. They pass untouched from Razor to the HTML output.

TIP This is different from the way HTML Helpers worked in legacy ASP.NET; HTML helpers often require jumping through hoops to set attributes in the generated markup.