Even better, you can also override attributes that are normally generated by a Tag Helper, like the `type` attribute on an `<input>` element. For example, if the `FavoriteColor` property on your `PageModel` was a `string`, by default Tag Helpers would generate an `<input>` element with `type="text"`. Updating your markup to use the HTML5 `color` picker type is trivial; set the `type` explicitly in your Razor view:

```
<input type="color" asp-for="FavoriteColor" />
```

TIP HTML5 adds a huge number of features, including lots of form elements that you may not have come across before, such as `range` inputs and `color` pickers. You can read about them on the Mozilla Developer Network website at http://mng.bz/qOc1.

For the remainder of section 18.2, you'll build the currency converter Razor templates from scratch, adding Tag Helpers as you find you need them. You'll probably find you use most of the common form Tag Helpers in every application you build, even if it's on a simple login page.

18.2.1 The Form Tag Helper

The first thing you need to start building your HTML form is, unsurprisingly, the `<form>` element. In listing 18.3 the `<form>` element was augmented with an `asp-page` Tag Helper attribute:

```
<form asp-page="Checkout">
```

The Tag Helper adds `action` and `method` attributes to the final HTML, indicating which URL the form should be sent to when it's submitted and the HTTP verb to use:

```
<form action="/Checkout" method="post">
```