You can see the generated hidden `<input>` at the bottom of the `<form>` in listing 18.4; it's named `__RequestVerificationToken` and contains a seemingly random string of characters. This field won't protect you on its own, but I'll describe in chapter 29 how it's used to protect your website. The Form Tag Helper generates it by default, so you generally won't need to worry about it, but if you need to disable it, you can do so by adding `asp-antiforgery="false"` to your `<form>` element.

The Form Tag Helper is obviously useful for generating the `action` URL, but it's time to move on to more interesting elements—those that you can see in your browser!

18.2.2 The Label Tag Helper

Every `<input>` field in your currency converter application needs to have an associated label so the user knows what the `<input>` is for. You could easily create those yourself, manually typing the name of the field and setting the `for` attribute as appropriate, but luckily there's a Tag Helper to do that for you.

The Label Tag Helper is used to generate the caption (the visible text) and the `for` attribute for a `<label>` element, based on the properties in the `PageModel`. It's used by providing the name of the property in the `asp-for` attribute:

```
<label asp-for="FirstName"></label>
```

The Label Tag Helper uses the `[Display]` `DataAnnotations` attribute that you saw in chapter 16 to determine the appropriate value to display. If the property you're generating a label for doesn't have a `[Display]` attribute, the Label Tag Helper uses the name of the property instead. Consider this model in