alternative validation library called *aspnet-client-validation*. I describe why you might consider this library and how to use it in this blog post: http://mng.bz/V1pX.

You can also load these files, whether you're using jQuery or aspnet-client-validation, from a content delivery network (CDN). If you want to take this approach, you should consider scenarios where the CDN is unavailable or compromised, as I discuss in this blog post: http://mng.bz/2e6d.

The Input Tag Helper tries to pick the most appropriate template for a given property based on `DataAnnotations` attributes or the type of the property. Whether this generates the exact `<input>` type you need may depend, to an extent, on your application. As always, you can override the generated `type` by adding your own `type` attribute to the element in your Razor template. Table 18.1 shows how some of the common data types are mapped to `<input>` types and how the data types themselves can be specified.

Table 18.1 Common data types, how to specify them, and the input element type they map to

Data type	How it's specified	Input element type
`byte, int, short, long, uint`	Property type	`number`
`decimal, double, float`	Property type	`text`
`bool`	Property type	`checkbox`
`string`	Property type, `[DataType(DataType.Text)]` attribute	`text`
`HiddenInput`	`[HiddenInput]` attribute	`hidden`
`Password`	`[Password]` attribute	`password`
`Phone`	`[Phone]` attribute	`tel`
`EmailAddress`	`[EmailAddress]` attribute	`email`
`Url`	`[Url]` attribute	`url`
`Date`	`DateTime` property type, `[DataType(DataType.Date)]` attribute	`datetime-local`