The Input Tag Helper has one additional attribute that can be used to customize the way data is displayed: `asp-format`. HTML forms are entirely string-based, so when the `value` of an `<input>` is set, the Input Tag Helper must take the value stored in the property and convert it to a `string`. Under the covers, this performs a `string.Format()` on the property's value, passing in the format string.

The Input Tag Helper uses a default format string for each different data type, but with the `asp-format` attribute, you can set the specific format string to use. For example, you could ensure that a `decimal` property, `Dec`, is formatted to three decimal places with the following code:

```
<input asp-for="Dec" asp-format="{0:0.000}" />
```

If the `Dec` property had a value of 1.2, this would generate HTML similar to

```
<input type="text" id="Dec" name="Dec" value="1.200">
```

Alternatively, you can define the format to use by adding the `[DisplayFormat]` attribute to the model property:

```
[DisplayFormat("{0:0.000}")]
public decimal Dec { get; set; }
```

NOTE You may be surprised that `decimal` and `double` types are rendered as `text` fields and not as `number` fields. This is due to several technical reasons, predominantly related to the way different cultures render decimal points and number group separators. Rendering as text avoids errors that would appear only in certain browser-culture combinations.

In addition to the Input Tag Helper, ASP.NET Core provides the Textarea Tag Helper. This works in a similar way, using the `asp-for` attribute, but it's attached to a `<textarea>` element instead: