```
<textarea asp-for="BigtextValue"></textarea>
```

This generates HTML similar to the following. Note that the property value is rendered inside the element, and `data-val-*` validation elements are attached as usual:

```
<textarea data-val="true" id="BigtextValue" name="BigtextValue"
    data-val-length="Maximum length 200." data-val-length-max="200"
    data-val-required="The Multiline field is required." >This is some text,
I'm going to display it
in a text area</textarea>
```

I hope that this section has hammered home how much typing Tag Helpers can cut down on, especially when using them in conjunction with `DataAnnotations` for generating validation attributes. But this is more than reducing the number of keystrokes required; Tag Helpers ensure that the markup generated is correct and has the correct `name`, `id`, and format to automatically bind your binding models when they're sent to the server.

With `<form>`, `<label>`, and `<input>` under your belt, you're able to build most of your currency converter forms. Before we look at displaying validation messages, there's one more element to look at: the `<select>`, or drop-down, input.

18.2.4 The Select Tag Helper

As well as `<input>` fields, a common element you'll see on web forms is the `<select>` element, or drop-down lists and list boxes. Your currency converter application, for example, could use a `<select>` element to let you pick which currency to convert from a list.

By default, this element shows a list of items and lets you select one, but there are several variations, as shown in figure 18.6. As well as the normal drop-down list, you could show a list box, add multiselection, or display your list items in groups.