Listing 18.5 View model for displaying select element drop-down lists and list boxes

```
public class SelectListsModel: PageModel
{
    [BindProperty]                                                  ❶
    public class InputModel Input { get; set; }                     ❶

    public IEnumerable<SelectListItem> Items { get; set; }          ❷
        = new List<SelectListItem>                                  ❷
    {                                                               ❷
        new SelectListItem{Value = "csharp", Text="C#"},            ❷
        new SelectListItem{Value = "python", Text= "Python"},       ❷
        new SelectListItem{Value = "cpp", Text="C++"},              ❷
        new SelectListItem{Value = "java", Text="Java"},            ❷
        new SelectListItem{Value = "js", Text="JavaScript"},        ❷
        new SelectListItem{Value = "ruby", Text="Ruby"},            ❷
    };                                                              ❷

    public class InputModel
    {
        public string SelectedValue1 { get; set; }                  ❸
        public string SelectedValue2 { get; set; }                  ❸
        public IEnumerable<string> MultiValues { get; set; }        ❹
    }
}
```

❶ The InputModel for binding the user's selections to the select boxes

❷ The list of items to display in the select boxes

❸ These properties will hold the values selected by the single-selection select boxes.

❹ To create a multiselect list box, use an IEnumerable<>.

This listing demonstrates several aspects of working with `<select>` lists:

- `SelectedValue1`/`SelectedValue2`—Used to hold the value selected by the user. They're model-bound to the value selected from the drop-down list/list box and used to preselect the correct item when rendering the form.