```
    <li class="nav-item">
        <a class="nav-link text-dark"
            asp-area="" asp-page="/Privacy">Privacy</a>
    </li>
</ul>
```

As you can see, each `<a>` element has an `asp-page` attribute. This Tag Helper uses the routing system to generate an appropriate URL for the `<a>`, resulting in the following markup:

```
<ul class="nav navbar-nav">
    <li class="nav-item">
        <a class="nav-link text-dark" href="/">Home</a>
    </li>
    <li class="nav-item">
        <a class="nav-link text-dark" href="/Privacy">Privacy</a>
    </li>t
</ul>
```

The URLs use default values where possible, so the `Index` Razor Page generates the simple `"/"` URL instead of `"/Index"`.

If you need more control over the URL generated, the Anchor Tag Helper exposes several additional properties you can set, which are used during URL generation. The attributes most often used with Razor Pages are

- `asp-page`—Sets the Razor Page to execute.
- `asp-page-handler`—Sets the Razor Page handler to execute.
- `asp-area`—Sets the area route parameter to use. Areas can be used to provide an additional layer of organization to your application.[1]
- `asp-host`—If set, the generated link points to the provided host and generates an absolute URL instead of a relative URL.
- `asp-protocol`—Sets whether to generate an http or https link. If set, it generates an absolute URL instead of a relative URL.