```
<environment include="Testing,Staging">
    <div class="warning">You are currently on a testing environment</div>
</environment>
```

This Tag Helper is a little different from the others you've seen before. Instead of augmenting an existing HTML element using an `asp-` attribute, the *whole element* is the Tag Helper. This Tag Helper is completely responsible for generating the markup, and it uses an attribute to configure it.

Functionally, this Tag Helper is identical to the C# markup (where the `env` variable contains the hosting environment, as described in chapter 10), but it's more declarative in its function than the C# alternative. You're obviously free to use either approach, but personally I like the HTML-like nature of Tag Helpers.

We've reached the end of this chapter on Tag Helpers, and with it, we've finished our main look at building traditional web applications that display HTML to users. In the last part of the book, we'll revisit Razor templates when you learn how to build custom components like custom Tag Helpers and view components. For now, you have everything you need to build complex Razor layouts; the custom components can help tidy up your code down the line.

Part 3 of this book has been a whistle-stop tour of how to build Razor Page applications with ASP.NET Core. You now have the basic building blocks to start making server-rendered ASP.NET Core applications. Before we move on to discussing security in part 4 of this book, I'll take a couple of chapters to discuss building apps with MVC controllers.

I've talked about MVC controllers a lot in passing, but in chapter 19 you'll learn why I recommend Razor Pages over MVC controllers for server-rendered apps. Nevertheless, there are some situations for which MVC controllers make sense.

Summary