- With Tag Helpers, you can bind your data model to HTML elements, making it easier to generate dynamic HTML while remaining editor friendly.
- As with Razor in general, Tag Helpers are for server-side rendering of HTML only. You can't use them directly in frontend frameworks, such as Angular or React.
- Tag Helpers can be standalone elements or can attach to existing HTML using attributes. This lets you both customize HTML elements and add entirely new elements.
- Tag Helpers can customize the elements they're attached to, add additional attributes, and customize how they're rendered to HTML. This can greatly reduce the amount of markup you need to write.
- Tag Helpers can expose multiple attributes on a single element. This makes it easier to configure the Tag Helper, as you can set multiple, separate values.
- You can add the `asp-page` and `asp-page-handler` attributes to the `<form>` element to set the `action` URL using the URL generation feature of Razor Pages.
- You specify route values to use during routing with the Form Tag Helper using `asp-route-*` attributes. These values are used to build the final URL or are passed as query data.
- The Form Tag Helper also generates a hidden field that you can use to prevent CSRF attacks. This is added automatically and is an important security measure.
- You can attach the Label Tag Helper to a `<label>` using `asp-for`. It generates an appropriate `for` attribute and caption based on the `[Display] DataAnnotation` attribute and the `PageModel` property name.