- Any extra additional `<option>` elements added to the Razor markup are passed through to the final HTML unchanged. You can use these additional elements to easily add a "no selection" option to the `<select>` element.
- The Validation Message Tag Helper is used to render the client- and server-side validation error messages for a given property. This gives important feedback to your users when elements have errors. Use the `asp-validation-for` attribute to attach the Validation Message Tag Helper to a `<span>`.
- The Validation Summary Tag Helper displays validation errors for the model, as well as for individual properties. You can use model-level properties to display additional validation that doesn't apply to just one property. Use the asp`-validation-summary` attribute to attach the Validation Summary Tag Helper to a `<div>`.
- You can generate `<a>` URLs using the Anchor Tag Helper. This helper uses routing to generate the `href` URL using `asp-page`, `asp-page-handler`, and `asp-route-*` attributes, giving you the full power of routing.
- You can add the `asp-append-version` attribute to `<link>`, `<script>`, and `<img>` elements to provide cache-busting capabilities based on the file's contents. This ensures users cache files for performance reasons, yet still always get the latest version of files.
- You can use the Environment Tag Helper to conditionally render different HTML based on the app's current execution environment. You can use this to render completely different HTML in different environments if you wish.

---

[1] I don't cover areas in detail in this book. They're an optional aspect of MVC that are often only used on large projects. You can read about them here: http://mng.bz/3X64.