```
            {                                                       ❿
                return NotFound();                                  ❿
            }                                                       ❿
            _service.UpdateRecipe(command);                         ⓫
            return Ok();                                            ⓫
        }
        catch (Exception ex)                                        ⓬
        {                                                           ⓬
            return GetErrorResponse(ex);                            ⓬
        }                                                           ⓬
    }

    private static IActionResult GetErrorResponse(Exception ex)
    {
        var error = new ProblemDetails
        {
            Title = "An error occurred",
            Detail = context.Exception.Message,
            Status = 500,
            Type = "https://httpstatuses.com/500"
        };

        return new ObjectResult(error)
        {
            StatusCode = 500
        };
    }
}
```

❶ This field would be passed in as configuration and is used to control access to actions.

❷ If the API isn't enabled, blocks further execution

❸ If the requested Recipe doesn't exist, returns a 404 response

❹ Fetches RecipeDetailViewModel

❺ Sets the Last-Modified response header to the value in the model

❻ Returns the view model with a 200 response

❼ If an exception occurs, catches it and returns the error in an expected format, as a 500 error

❽ If the API isn't enabled, blocks further execution

❾ Validates the binding model and returns a 400 response if there are errors

❿ If the requested Recipe doesn't exist, returns a 404 response

⓫ Updates the Recipe from the command and returns a 200 response

⓬ If an exception occurs, catches it and returns the error in an expected format, as a 500 error