to review team progress, assign tasks, and generate reports before key meetings. She clicks on the tab labeled Team Reports, hoping to review progress updates before a morning meeting.

Alice opens the dashboard from her laptop at home and clicks on the Team Reports tab, hoping to review her team's weekly performance summary. That simple click kicks off a sophisticated process behind the scenes.

The Policy Enforcement Point (PEP)—in this case, embedded in the application—intercepts the request. It recognizes that Alice is trying to view a report, which is a protected resource, and it needs to know: Is she allowed to do that right now, from this device, in this context?

The PEP sends the request to the Policy Decision Point (PDP), which is responsible for evaluating access requests. The PDP reviews the key facts:

- The principal is Alice.
- The action is `view`.
- The resource is a team report.
- The conditions include the current time (9:17 PM), her device (company-issued laptop), and her network (home, not corporate).

But the PDP needs more information to make an informed decision. It turns to the Policy Information Point (PIP). The PIP retrieves Alice's attributes from the company's identity system: she's in the Project Managers group, her current session originates from a registered device, and her access to reports is typically allowed between 7 AM and 8 PM.

Now the PDP has what it needs. It checks the policies:

> Alice is in the right role.
>
> She's using a trusted device.
>
> But it's outside of approved hours.

The PDP returns a `deny` decision to the PEP, including the specific policy that prompted the denial. Using the information about the decision, the