```
{
  "principal": { "type": "User", "id": "kate@custco.com" },
  "action": "collab:doc.meta.read",
  "resource": { "type": "Workspace", "id": "custco-sales" },
  "context": {
    "token_scopes": ["collab:workspace.read","collab:doc.meta.rea
d"],
    "origin_service": "bi-explorer"
  }
}
```

Cedar evaluates this request against the Customer Collaboration platform's policy for workspace membership:

```
permit(
  principal in ACME::User,
  action == Action::"collab:doc.meta.read",
  resource in ACME::Workspace
)
when { principal in resource.members };
```

Because Kate is a member of the `custco-sales` workspace, Cedar returns `allow`, and the gateway forwards the call to the Collaboration API. If BI Explorer tries to fetch documents from a workspace Kate does not belong to, Cedar would return `deny`, and the API call would be blocked.

This combination of OAuth scopes and Cedar policy makes sure that BI Explorer can read only the metadata Kate has consented to and only within workspaces where she already has access.

EXAMPLE: CUSTCO'S TASK APP (CLIENT CREDENTIALS TOKEN)

CustCo's Task App performs a background sync that aligns tasks with ACME's Customer Collaboration workspaces. It uses the Client Credentials grant to authenticate itself, so the access token's subject is the integration principal, not a person. During setup, a CustCo admin restricted the app to two workspaces: `custco-sales` and `custco-support`.

When the app needs to create a task for a new action item in `custco-sales`, it sends an API request like this: