1. **System policies**. Internal rules governing operational or administrative actions within C³
2. **Global application policies**. Created and maintained by ACME to define the platform's trust boundaries
3. **Tenant policies.** Defined within each tenant's namespace; govern collaboration using ReBAC

Table 13.3 presents these three layers, outlines who manages them and their scope, and provides an example of human-readable policy.

Table 13.3 Policy layers in the C³ authorization model

Policy layer	Managed by	Typical scope	Example
System	ACME platform engineering and operations teams	Entire platform and supporting automation	Allow scheduled backup jobs to read all tenant metadata.
Application	ACME C³ product team	The C³ application itself; multi-tenant governance	Only ACME employees with compliant devices may perform cross-tenant support actions.
Tenant	Customer tenants	Collaboration and sharing within a tenant	Permit sharing only with users in the same verified email domain.

Together, these layers define a nested hierarchy of scope. System policies form the outermost boundary, governing the entire C³ platform and its automation. Inside that boundary, application policies control how the Customer Collaboration Cloud operates as a multi-tenant service. At the center, tenant policies manage collaboration within each tenant's namespace. System policies are authored by ACME's platform engineering team under the governance of the identity team, ensuring that even automated or administrative actions—such as backups, monitoring, or replication—follow the same authorization and audit standards as customer-initiated requests.

13.5.7 Shared schema and type safety

All three layers use a shared Cedar schema, ensuring that each policy speaks the same language for entities, actions, and attributes: