```
{
  "type": ["VerifiableCredential", "ReimbursementDelegationCredentia
l"],
  "issuer": "did:web:finance.acme.example",
  "credentialSubject": {
    "id": "did:web:agents.partnerpay.example:reimbursement-agent",
    "capability": "contractor.reimbursement.pay",
    "constraints": {
      "max_amount": 250,
      "currency": "USD",
      "contractor_id": "ctr-44721",
      "expense_category": [
        "travel",
        "meals",
        "supplies",
        "software"
      ],
      "requires_receipt": true,
      "purpose": "pay approved contractor reimbursement",
      "expires": "2026-04-30T23:59:59Z"
    }
  }
}
```

The credential carries the delegation across domains but does not decide if a payment is permitted. The partner’s Cedar policies still review each request using the credential’s claims as inputs.

If the payment is processed successfully, the partner returns a signed receipt to ACME. Both systems record the result, updating their internal reputation databases. Over time, these interactions help each side evaluate if the other agent consistently keeps its promises.

Cross-domain delegation relies on more than just credentials. It emerges from the interaction of policies that constrain behavior, promises that communicate intent, and reputations that serve as records of past interactions’ outcomes. Together, these mechanisms allow independent domains to cooperate while still enforcing their own authorization boundaries. In this way, authorization architecture becomes one of the core mechanisms that makes a practical society of agents possible.