- AWS CLI v2 is installed and configured. You can check the installed version by running `aws –version`.
- You must choose a region where AVP is available. You can set your region to `us-east-1` using the CLI tool: `aws configure set region us-east-1`.
- JSON tools are also helpful. For instance, we'll use `jq -Rs` to wrap the Cedar schema string.

Once these are configured, we can begin by setting up a policy store.

> ***TIP***
>
> To install the AWS CLI, see "Getting started with the AWS CLI" (https://docs.aws.amazon.com/cli/latest/userguide/cli-chap-getting-started.html). The documentation for the AVP CLI commands can be found here: https://docs.aws.amazon.com/cli/latest/userguide/cli_verifiedpermissions_code_examples.html.

A.2 Create a policy store

The initial step is to create a new policy store in AVP. This serves as the container for your schema, policies, and entities. You can do this either through the AWS Console or using the AWS CLI. For example, the command creates a policy store and puts the ID in the variable `STORE_ID`:

```
STORE_ID=$(
  aws verifiedpermissions create-policy-store \
    --validation-settings "mode=STRICT" \
    --query policyStoreId --output text
)
echo "$STORE_ID"
```

Using `strict` mode causes AVP to enforce type checks against our schema and prevents us from uploading malformed policies.