Begin by cloning the repository and opening it in an AI-enabled editor such as Cursor. If you use Emacs-style key bindings, enable them in Cursor's settings before continuing.

The repository is organized into a small number of directories:

- `cedar/` contains the Cedar schema, entity data, and policy files reused from Appendix A. These files are the source of truth for all examples in this appendix.
- `examples/` contains representative authorization requests used to illustrate policy behavior.
- `tests/` contains expected decisions associated with those requests.
- `ai/cursor/` contains tool-specific guidance for using Cursor safely, including a starter prompt and human review guidelines.

Before proceeding, read the files in `ai/cursor/`, starting with the `README`, followed by `starter-prompt.md` and `authoring-guidelines.md`. These documents describe how AI assistance is intended to be used in this repository and the constraints that apply to all AI-generated output.

You do not need to modify any files yet. The goal in this section is simply to become familiar with the structure of the repository and to ensure that Cursor can see the schema and policy files together.

B.4 Providing the right context to the AI

AI-assisted policy authoring works best when the model has access to the same artifacts a human reviewer would use. Before asking the AI to draft or modify a policy, make sure it can see the schema, the existing policies, and at least one concrete example of policy behavior.

Begin by opening the following files in your editor:

- `cedar/acme.cedarschema`
- All policy files under `cedar/policies/`
- `examples/sample-request.json`