identity to authoritative sources. We will consider enrollment in more depth in the next section.

### 3.3.2 Propagate

When a digital relationship is created, updated, or terminated, the changes must be distributed across relevant systems to ensure that the systems and services that rely on it have up-to-date information. This may involve synchronizing identity data with directory services, updating role assignments, or pushing access credentials to federated systems.

Several protocols support propagation. These protocols enable authentication, authorization, and identity management to remain consistent across an organization's infrastructure. Some of the commonly used protocols include SCIM (System for Cross-domain Identity Management), which automates user provisioning and de-provisioning across multiple systems; LDAP (Lightweight Directory Access Protocol), which is a directory service protocol for querying and managing account data; SAML (Security Assertion Markup Language), which enables single sign-on (SSO) by passing identity assertions between identity providers (IdPs) and service providers (SPs); and OpenID Connect (OIDC), which is an authentication and authorization framework that propagates identity attributes in signed tokens.

### 3.3.3 Use

This is the active phase, where identity relationships are verified through authentication, and authorization governs what actions an identity can perform. During this phase, the system should continuously verify that the relationship remains valid based on contextual signals, policies, and real-time risk analysis.

### 3.3.4 Update

Identity relationships are not static—they evolve as users change roles, update credentials, or gain new permissions. This process might be simple or complex, depending on what kinds of functions the relationship is designed