```
# Mac
echo $PACT_BROKER_BASE_URL
echo $PACT_BROKER_TOKEN
# Windows
echo %PACT_BROKER_BASE_URL%
echo %PACT_BROKER_TOKEN%
```

Now, you're ready to publish the contract! To do so, let's create a new script in our package.json called `publish:pact`, which uses the `pact-broker` command, which comes built-in when the Pact library has been installed:

```
"scripts": {
    "start:provider": "cross-env PORT=3001 node provider/provider-service.js",
    "test:web:consumer": "jest consumer-web/consumer-contract.spec.js",
    "publish:pact": "pact-broker publish ./pacts --consumer-app-
version=1.0.0 --tag=main --broker-base-url=$PACT_BROKER_BASE_URL
--broker-token=$PACT_BROKER_TOKEN"
  }
```

This command will publish the contract stored in my pacts folder to PactFlow. We'll use the `--consumer-app-version` flag and pass the `1.0.0` value to it for now. In chapter 10, we'll look at how to set better versions for our contracts. Next, we'll use the `--broker-base-url` and `--broker-base-token` flags and pass in the environment variables I set for my broker URL and token.

Make sure to save all the changes. To publish the contract, open your terminal, and type in the following command:

```
npm run publish:pact
```

You should see a message in your terminal, similar to figure 4.9: