Create a function with the Pact annotation, along with parameters for the provider and consumer, shown in listing 5.9. The provider is the movie API service, and the consumer is the Android app. Each interaction will then be assigned to this consumer-provider relationship. Therefore, it's really important to keep the naming convention consistent and make sure the provider name is being referenced the same way across different consumers as well. The builder parameter is what we'll use to construct the Pact contract, and the output type of the builder will be V4Pact.

Listing 5.9 Create Pact

```
import au.com.dius.pact.consumer.dsl.PactDslWithProvider
import au.com.dius.pact.core.model.annotations.Pact
import au.com.dius.pact.core.model.V4Pact

@Pact(provider = "MoviesAPI", consumer = "MoviesAndroidApp")
fun createPact(builder: PactDslWithProvider): V4Pact {
```

V4Pact refers to version 4 (https://mng.bz/EOYO) of the Pact file format, supported in the Pact-JVM implementation. The V4 file format is a JSON text file with the following sections:

- consumer
- provider
- interactions
- metadata

The first two sections, the consumer and the provider, state which parties the contract is between. The third section, interactions, contains all the details of the consumer request and expected response. Think of an interaction as a test scenario. Each scenario is added to the contract for each consumer interaction with the provider. For example, the consumer wants to display all movies to the user by making a `GET` request to the `'/movies'` endpoint. The consumer also has an admin portal that adds movies to the list by making a `POST` request to the `'/movies'` endpoint. Each scenario has different request content and expected responses. The fourth section contains any metadata related to which version of the Pact file is being used and which implementation, for example, pact-jvm.