Listing 5.19 Matcher types example

```
PactDslJsonBody body = new PactDslJsonBody()
    .stringType("name", "Lewis")
    .integerType("no.")
    .date("todaysDate", "mm/dd/yyyy", date)
    .ipAddress("localAddress");
```

The matching types chain to the Pact DSL JSON body method. Some of the type methods can also take an optional argument, which is used as the example values within the Pact contract file. Matchers aren't exclusive to response bodies either. They can be applied to URL paths, headers, and query parameters.

Imagine we have an API that takes a movie name as the ID within the URL path, for example, "/movie/jaws". The `matchPath` method can be used to substitute the movie name with a regular expression. The method used in listing 5.7 path (`"/movies"`) earlier in the chapter would then be substituted with the `matchPath` method, as follows.

Listing 5.20 Match path

```
builder
  .given("test state")
  .uponReceiving("a movie id")
  .matchPath("/movies/[a-z]+")
```

Imagine the API exposes an endpoint to add a new movie to the database, and that this API endpoint requires an API token header to authorize the request. The `matchHeader` method can be used in this example for the provider to be able to substitute the API token with a real one when they run the test.

Listing 5.21 Match headers

```
.path("/movies")
.method("POST")
.matchHeader("API-Token", "xxx")
```

Imagine the `"/movies"` endpoint took a query parameter `"id"`. The `matchQuery` method can be used, taking three arguments: (1) the query parameter key value, (2) the regular expression for the value, and (3) the example value of the movie value. The provider will substitute the example value when running the test against their data set, as shown in listing 5.22.