and run the command `npm run start:provider` before running your provider contract test. Just make sure that the movies API is up and running locally!

SETTING UP THE PROVIDER VERIFIER OPTIONS

Pact provides an interface called `Verifier` to represent the provider for our test. To create the options for our provider, add the following code:

```
const options = {
  provider: 'MoviesAPI',
  providerBaseUrl: `http://localhost:${port}`,
  pactBrokerUrl: process.env.PACT_BROKER_BASE_URL,
  pactBrokerToken: process.env.PACT_BROKER_TOKEN,
  providerVersion: '1.0.0',
  publishVerificationResult: true,
  consumerVersionTags: ['main'],
};

const verifier = new Verifier(options);
```

In addition to these options, the `options` object contains other pieces of metadata:

- The `provider` name, `MoviesAPI`, should be the same name per the consumer contract.
- `providerBaseUrl` represents how to access our provider.
- `pactBrokerUrl` and `pactBrokerToken`, which we first set up in chapter 4, are required to download the consumer contract.
- `providerVersion` is hard-coded to `1.0.0` for now. We'll look at how to provide better versions in chapter 8.
- `publishVerificationResults` is set to `true` and will publish the verification results to our pact broker.
- `consumerVersionTags` is an array of consumer versions that we're going to verify. In this setup, the consumer version is set to `main`.

Once the options have been defined, we create a new instance of `Verifier` and pass in the options to that instance.