RUNNING THE PROVIDER CONTRACT TEST

To run the provider verification, run the following command in your terminal again:

```
npm run test:provider
```

You should now see that two requests have been verified successfully by the provider. If you also look at the logs closely, you'll see a similar output as in figure 6.8.

```
2023-12-01T13:13:37.819737Z  INFO ThreadId(09) pact_verifier: Running setup provider state change handler '
Has a movie with specific ID' for 'a request to a specific movie'
2023-12-01T13:13:37.936919Z  INFO ThreadId(09) pact_verifier: Running provider verification for 'a request
to a specific movie'
2023-12-01T13:13:37.936952Z  INFO ThreadId(09) pact_verifier::provider_client: Sending request to provider
at http://127.0.0.1:65170/
2023-12-01T13:13:37.936954Z  INFO ThreadId(09) pact_verifier::provider_client: Sending request HTTP Request
 ( method: GET, path: /movie/100, query: None, headers: None, body: Missing )
```

Figure 6.8 Test logs explaining that the provider state change handler was run first before running the provider verification.

When you finish this chapter, don't forget to commit all the changes you've introduced locally to your forked GitHub project.

6.4 Provider contract tests between a mobile app and data provider

From chapter 5, we also created a consumer contract between a mobile app and the movies API. Because we provided the same provider name as part of the mobile consumer setup, as shown in the following code snippet, no additional steps are required to verify the mobile contract: